



Technical Data Sheet

Resistant Multi-Pro is a new age medium density multi purpose Magnesium Silicate board. A highly durable, non combustible board for use in applications requiring a combination of sound insulation, moisture resistance and good performance in fire.


The board will not rot and can be used as an alternative to chipboard, plywood or wood based cement particle board, where a greater dimensional stability is required. The board is versatile and suitable for an extensive range of internal and external construction applications.

Retro-Fit

Solid/Partition Walls

Key:

- 1 Brickwork
- 2 Vapour Control Membrane
- 3 Insulation
- 4 9/12 mm **Multi-Pro** foil backed
- 5 Interior Skimcoat
- 6 Interior Finish Render
- 7 Steel Framework
- 8 9mm Internal **Multi-Pro**
- 9 Insulation
- 10 Timber Flooring
- 11 Concrete Base Floor



MANUFACTURE

Resistant Multi-pro is manufactured using inorganic substances, CaCO₃, MgO, MgCl₂, and alkaline resistant fibreglass mesh.

The product is naturally cured using no energy through cold fusion unlike similar competitive products on the market which use autoclaving technology. This ensures that Resistant Multi-Pro has a relatively low impact on the environment. Multi-Pro achieves its superior strength and flexibility by the introduction of two layers of alkaline resistant glass fibre mesh. Consistent high quality of the product is maintained and monitored through a sophisticated digitally controlled process to ensure a superior finished board always reaches our commitment to quality assurance.

TYPICAL USES

It is ideal for applications requiring a combination of these properties, for example:

Wall Cladding and infill Panels
Fire Resistant Internal Panels
High impact, Fire and Acoustic rated partitions
Door Skins
Soffits / Dormers
Plant Rooms



Technical Data Sheet

Technical SPECIFICATION

Test Subject	Test	Result
Density Dry (ex works)		1050 kg/m ³ (+/- 10%)
Modulus of Rupture	BSEN 310	20 Nmm ²
Modulus of Elasticity	BSEN 310	4540 Nmm ²
Impact Strength (Brinell)		34 Nmm ²
Vapour Permeability	BSEN 12086	100 mg/m ² /h
Thermal Conductivity at 50°	BSEN 594	0.26 w/m ² /°k
Fire Test	A1 Euroclass	Class Non-Combustible
Change in thickness (After immersion in water)	BSEN 317	0 - 0.1% Nmm ²
Tensile Strength (Perpendicular to plane)	BSEN 319	2.11 Nmm ²
Screw Withdrawal Strength	BSEN 320	1.15 KN
Cyclic tests in humid conditions	BSEN 321	
Average Thickness Swelling	BSEN 321	0
Average Tensile Strength	BSEN 321	2.04 Nmm ²
Moisture Content	BSEN 322	3.6%
Fire Resistance Steel	BSEN 1364 - 1	60 minutes

DIMENSIONS

RESISTANT Multi-Pro is supplied as a rectangular board with square edges and white in colour.

Thickness: 3 - 6 - 9 - 12 mm
 Sizes: 1200 x 2400 / 3000 mm


Special size requirements and thicknesses are also available upon request depending on quantity.

TOLERANCES


Length and Width: + / - 2mm
 Thickness: + / - 0.2mm
 Edge Straightness: 1mm / metre
 Squareness of edge: < 3mm




Technical Data Sheet



RESISTANT boards should be stored flat, raised from the ground on a pallet, in dry conditions indoors and be under cover. Boards should not be leant upright for long periods of time



Boards should always be lifted by 2 people and not dragged across each other to prevent unnecessary scratching or damage



Any moisture allowed to infiltrate between the sheets will cause permanent surface staining. They should be protected from the weather and other trades on site at all times



Boards should be carried on edge and extra precaution should be taken to protect the visible front edge and corners

SUPERIOR ATTRIBUTES

Apart from accepting a variety of painted/polished finishes, RESISTANT boards provide an excellent compatible surface to a wide range of finishing materials i.e. paints, tiles, veneers, laminates or indeed any finishing option that comes to the creative mind of an architect or interior designer. The acceptance of RESISTANT in the highly competitive international market stands testimony to its superior attributes



Fire Rated, Non-Flammable , Non-Combustible

*Non-Combustible to BS 476 Part 4
BS EN ISO 1182 - Euro Class A1*



Thermal Insulation Properties

Provides a high level of thermal movements during hot and cold cycles (Thermal Shock)



Impact Resistant

An ability to withstand abuse, including surface impact - 34 N/mm



Low Carbon Manufacturing Process

A natural cured process with a chemical reaction using low levels of heat and a lengthy drying out stage



Moisture & Water Resistant

RESISTANT boards will not physically deteriorate when subjected to water or moisture.



Sound Insulation

Provides excellent sound insulation for walls, floors and ceilings



Rodent Resistant

Resistant to rodent infestation like mice, rats and insects



Easy and Fast to work

Easy and simple to prepare and attach. Rough surface allows application of renders or direct paint / wallpaper



Mould Resistant

Unlike paper faced/wood based products, RESISTANT does not contain cellulose, limiting mould growth



Breathability

Ensures a healthy, durable working building with a natural ability to absorb and release moisture



Chemically Stable

Produced from natural inorganic raw materials, resulting in a strong, durable chemically stable board



Non-Hazardous to health

Will not cause harm to persons and/or the environment. Produced without asbestos or other inorganic fibres