



# WP7-201 Spray & Seal

## RUBBER BASED REPAIR

- ✓ Immediately waterproof - immediately protected.
- ✓ Compatible with most surfaces including gutters.
- ✓ Instant protection against water & rust.
- ✓ Anti-Corrosive, suitable for metal components.
- ✓ For indoor and outdoor use.
- ✓ Remains flexible & can be sanded and painted.

### Technical Info

- Composition: rubber / synthetic resin.
- Odor: solvent.
- Colour: black.
- Consistency: semi-liquid resistant to sagging.
- Relative density: 0.8 (+/- 0.03).
- Application temperature: between + 15°C and + 25°C.
- Temperature resistance: from -40°C to + 90°C.
- Waterproof: immediately.
- Skin formation (0.5 mm thickness at 20°C, 50% R.H.): 25 minutes.
- Time between 2 layers (0.5 mm thickness at 20°C, 50% R.H.): 10 minutes.
- Complete drying (0.5 mm thickness at 20°C, 50% R.H.): 90 minutes.
- Paintable: yes.
- Resistance: water, seawater, oil, weak acids and bases.
- Shelf life: 24 months, in a dry room between + 10°C and + 30°C.

### Packing

WP7-201 Instant Waterproof - aerosol 500ml      602040000

### Product

#### Characteristics

Tec7 Spray & Seal can be used on hundreds of applications whether sealing, repairing, protection and is compatible with all surfaces. Tec7 Spray & Seal forms a tenacious, elastic waterproof coating that protects against shocks, stone chips and impact, while also reducing vibration and noise. Sandable after curing and paintable.

#### Applications

- Emergency repair of small leaks in roofs.
- Sealing leaking gutters.
- Sealing screw and drill holes.
- Anticorrosion coating of metal components.
- Protects auto parts against stone chips.
- Sealing roof screws in corrugated sheets.
- Protecting and sealing parts of caravan, mobile home, trailer,...
- Protecting parts of boats against splashing (sea) water.

## Use

---

- Apply onto a clean and dry substrate. If necessary, clean with Tec7 cleaner and/or Multiclean.
- Sand smooth surfaces and protect surrounding materials if necessary.
- Shake the can well for 1 minute.
- Apply from a distance of 25-40 cm from the surface.
- Ensure you apply a thin layer first and then build up to a layer thickness of approximately 0.5 mm.
- Please allow 10 minutes evaporation time between two layers.
- Empty the nozzle by spraying with the can upside down.

Clean tools immediately with Tec7 Cleaner and hands with Powerwipes or similar type product. Do not use in the rain, strong wind or on very warm surfaces. Can be painted with most paints and lacquers after 90 minutes. Test adhesion on plastics, powder coatings, exotic woods and bituminous materials. Do not use in ponds and not water pressure resistant.

1 aerosol 500 ml = +/- 1m<sup>2</sup> (+/- 0.5 mm layer thickness)