

PRODUCT DATA SHEET

EVERBUILD® ONE STRIKE FILLER®

READY-MIXED, QUICK-DRYING, REVOLUTIONARY LIGHTWEIGHT FILLER.

PRODUCT DESCRIPTION

EVERBUILD® ONE STRIKE FILLER® is a revolutionary ready-mixed lightweight filler for the preparation of numerous surfaces prior to painting or wallpapering. Based on high strength lightweight polymeric fillers, the product outperforms conventional fillers in most applications. Designed for professional and D.I.Y use. EVERBUILD® ONE STRIKE FILLER® finishes smooth, requiring little or no sanding and is ready to paint or wallpaper in just 30 minutes.

USES

Fills gaps and holes in:

- Plaster
- Brick
- Stone
- Wood
- Render

CHARACTERISTICS / ADVANTAGES

- Fills up to 75mm deep in one application - No need to build up layers of filler.
- Easy to use - lightweight paste is incredibly easy to apply.
- No sanding required - finishes to a smooth surface.
- No sagging - the lightweight properties of EVERBUILD® ONE STRIKE FILLER® prevent sagging even on ceilings.
- Non-shrink - will not shrink back whilst drying.
- Quick drying - ready to paint/paper in just 30 minutes.
- Overpaintable with most solvent based and emulsion paints.
- Overstainable.
- Internal/external use.
- Dries brilliant white.

Movement Accommodation	Low
Maximum Fill	75mm in one coat - Further layers may be built up
Maximum Width	50mm
Application Temperature	5°C - 30°C
pH	7.5 - 9.7 (tub) 8.5 - 9.9 (cartridge)

PRODUCT INFORMATION

Packaging	250ml, 450ml, 1Ltr, 2.5Ltr & 5Ltr Tubs 300ml Cartridge
Appearance / Colour	Lightweight brilliant white paste
Shelf Life	24 months from date of manufacture when stored according to manufacturers instructions.
Storage Conditions	Store between 5 - 25°C
Density	0.28 - 0.35 g/cm ³ (tub) 0.48 - 0.53 g/cm ³ (cartridge)
Solid Content	approx. 60% w/w

APPLICATION INFORMATION

Drying time

30 minutes at 20°C 50% R.H.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be clean, dry, free from dust, grease and other contamination.

APPLICATION

Tub

Apply direct from tub with spatula/spreader. Smooth over surface and allow to dry. Sanding is not normally required although the product may be sanded if required.

Cartridge

Remove cap and cut nozzle to required aperture. Squeeze directly into hole or crack and level with a filling knife. Sanding is not normally required although the product may be sanded if required.

LIMITATIONS

- Do not use to fill plastic or metals.
- Do not apply when rain is imminent (external use)
- Do not apply in temperatures (ambient and surface) below 5°C.
- Freezing damages the product

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Consult MSDS for full list of hazards.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
EVERBUILD® ONE STRIKE FILLER®
May 2019, Version 02.01
020406010020000031

EVERBUILDONESTRIKEFILLER-en-IE-(05-2019)-2-1.pdf