



BLUE DIAMOND STL
GLOBAL REACH, PERSONAL SERVICE

SAFETY DATA SHEET

According to Regulation (EU) No 830/2015

ProSolve™ Primer Spray Aerosol (500ml)

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

Trade Name: ProSolve™ Primer Spray Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses: To provide a base coating.

1.3. Details of the supplier of the safety data sheet

Company Name: Blue Diamond STL

Company Address: Sandall Stones Road, Kirk Sandall Industrial Estate, Doncaster, South Yorkshire,
DN3 1QR

Tel: +44 (0) 1302 310 113

E-mail: enquiries@bdstl.com

Web: www.bdstl.com

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

Hazard classes and Hazard categories	Hazard Statements
Aerosol 1	H222, H229
Aquatic Chronic 2	H411

2.2. Label elements Hazard pictograms:

Hazard pictograms:



Signal word: Danger

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements:

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards Results of PBT and vPvB assessment:

Product has an anesthetic effect.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / Information On Ingredients

Description

A mixture of resins, additives, organic solvents and organic gases.

3.1. Substances N/A

3.2. Mixtures Description: Hazardous Ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
95-47-6	601-022-00-9	Xylene	10-15%	R10 Xn; R20/21 Xi; R38
111-76-2	603-014-00-0	2-Butoxyethanol	5-10%	Xn; R20/21/22 Xi; R36/38
28701-67-9		Isodecyloxypropylamine acetate	<1%	C; R35
107-98-2	603-064-00-3	1-Methoxy-2-Propanol	5-10%	R10
67-64-1	200-662-2	Propan-2-one	40-60%	R11, R36, R66, R67
106-97-8	203-448-7	Butane	10-30%	F+; R12
74-98-6	200-827-9	Propane	10-30%	F+; R12

Contains no known PBT's or vPvB's

SECTION 4: First Aid Measures

4.1. Description of first aid measures

General information:

Remove contaminated soaked clothing immediately.

Inhalation:

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

Skin Problem:

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

Eye:

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

Ingestion:

Do not induce vomiting.

Medical treatment.

4.2. Most important symptoms and effects, both acute and delayed: No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed: No information available.

SECTION 5: Firefighting Measures

5.1. Extinguishing media

Suitable: Recommended use: Alcohol resistant foam, carbon dioxide (CO₂), dry powder, water spray. Do not use water jet. Cool containers with spray water.

Unsuitable: Do NOT use high pressure inert gas or water jets.

5.2. Special hazards arising from the substance or mixture: May lead to formation of explosive/easily ignitable vapour air mixtures. Danger of bursting.

5.3. Advice for fire-fighters: Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional Information: Vapours are heavier than air and will spread on the ground. Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions:

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

6.2. Environmental protection measures

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

6.4. Reference to other sections:

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Advice on Safety Handling:

Keep, the aerosol in a cool, dry place. Exclude sources of heat, sparks and open flame. Do not use sparking tools around aerosols. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. For personal protection, see section 8. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits. Never apply pressure to the aerosol, the aerosol is a pressurised object and may explode if pressure is applied.

General protective measures:

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs. Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material. Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air. Avoid effect of heat.

Use explosion-proof equipment / fittings and non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F). Store container at cool and aired place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure Controls / Personal Protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

Name	Long term exposure limits – 8hr time weighted average	Short term exposure limit – 15 minute reference period	Type	Ref
Xylene	WEL (8 hrs) WEL (15mins)	441mgm ⁻³ 662mgm ⁻³	N/A	
2-Butoxyethanol	25ppm	150ppm	WEL Sk Bmgv	EH40
1-Methoxy-2-Propanol	100ppm (375mgm ⁻³)	560mgm ⁻³	WEL Sk	EH40
Propan-2-one	1810mgm ⁻³	3620mgm ⁻³	WEL	SUP

“Sk” indicates a risk of absorption through the skin.

“Bmgv” indicates a biological monitoring guidance value.

“WEL” indicates a Workplace Exposure Limit. WEL’s are taken from the current version of EH40 except those marked “SUP” which are assigned by the supplier of the substance.

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

Tightly fitting goggles

Other protection measures

Protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance: Aerosol

Odour: Solvent-like

Colour: Black or White

pH (20°C): Not determined

Boiling Point: Not Applicable

Melting point / Freezing point: not determined

Flash point: Not applicable (Aerosol)

Vapourisation rate: Not determined

Flammable (solid): Not determined

Flammability (gas): Not determined

Ignition temperature: Not determined

Self ignition temperature: Not determined

Lower explosion limit: Not determined

Upper explosion limit: Not determined

Vapour pressure: Not determined

Relative density: Not determined

Vapour density: Not determined

Solubility in water: Not determined

Solubility/other: Not determined

Partition coefficient n- octanol/water (log P O/W): Not determined

Decomposition temperature: Not determined

Viscosity dynamic: Not determined

Viscosity kinematic: Not determined

Oxidising properties: Not determined

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information: No further relevant information available

SECTION 10: Stability and Reactivity

10.1. Reactivity: No

10.2. Chemical stability: No further relevant information available

10.3. Possibility of hazardous reactions: Possibility of hazardous reaction

10.4. Conditions to avoid: Keep away from heat. Formation of explosive gas/air mixtures.

10.5. Incompatible materials: No further relevant information available

10.6. Hazardous decomposition products: No further relevant information available

Thermal decomposition: No decomposition if used as directed.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 2000 mg/kg	Rat		Information concerns to main component.
LD50 acute dermal	1100 mg/kg			Xylene

LC50 acute inhalation	> 5 mg/l (4 h)	Rat		Aluminium
Irritability skin	irritant			
Irritability eye	irritant			

Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation. Irritates respiratory tract.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals. Other hazardous properties may not be excluded.

SECTION 12: Ecological Information

12.1. Toxicity

No information available.

12.2. Persistence and degradability: No information available.

12.3. Bioaccumulative potential: No information available.

12.4. Mobility in soil: No information available.

12.5. Results of PBT and vPvB assessment: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects: No known significant effects or critical hazards

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Waste Code Number

08 01 11*

Name of Waste

waste paint and varnish containing organic solvents or other dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

SECTION 14: Transport Information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number:	1950	1950	
14.2. UN proper shipping name:	AEROSOLS	AEROSOLS (ZINC POWDER)	Aerosols, flammable
14.3. Transport hazard class(es):	2.1	2.1	2.1
14.4. Packing group:	-	-	-
14.5. Environmental hazards:	Yes	Yes	Yes

14.6. Special precautions for user

No information available

14.7. Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code:

Not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1

Tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

MARINE POLLUTANT

Transport as limited quantities according to 3.4 IMDG Code is possible.

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

SECTION 15: Additional Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC Standard

VOC Content	0%
VOC Value	None

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other Information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed. For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU- directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H261	In contact with water releases flammable gases.

- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Issued By: Blue Diamond STL

OUR BRANDS



Blue Diamond STL, Sandall Stones Industrial Estate, Doncaster,
South Yorkshire, DN3 1QR

+44 (0)1302 310 113 enquiries@bdstl.com www.bdstl.com

ProSolve, Sapphire and Warrior are trademarks of Blue Diamond STL

Reg in England No: 5230722 VAT Reg No: 381 3533 58