

DRAINEX

Page: 1

Compilation date: 22/12/2015 Revision date: 23/01/2020 Revision No: 5

# Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DRAINEX

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Alkaline Drain Cleaner.

# 1.3. Details of the supplier of the safety data sheet

Company name:	Excel Industries	
	Coolmine Industrial Estate	
	Clonsilla Rd	
	Dublin 15	
	Ireland	
Tel:	+353 18118701	
Fax:	+353 18118786	
Email:	sales@excel-industries.com	

# 1.4. Emergency telephone number

Emergency tel: Emergency medical information: 8am-10pm (seven days) Contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

# Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Hazard pictograms: GHS05: Corrosion



DRAINEX

Signal words:DangerPrecautionary statements:P102: Keep out of reach of children.P260: Do not breathe dust/fumes/gas/mist/vapours/spray.P280: Wear protective gloves/protective clothing/eye protection/face protection.P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomitingP303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.Rinse skin with water .P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for<br/>breathing.Haz. ingredients (labe):SODIUM HYDROXIDE

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

3.2. Mixtures

# Hazardous ingredients:

#### SODIUM HYDROXIDE

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
215-185-5	1310-73-2	-	Skin Corr. 1A: H314	1-10%	
ACID PHOSPH	ACID PHOSPHATE ESTER				
609-691-9	39464-70-5	-	Skin Irrit. 2: H315; Eye Dam. 1: H318	1-10%	
ALCOHOLS, C12-14 (EVEN NUMBERED), ETHOXYLATED (CAS: 68439-50-9)					
932-106-6	68439-50-9	-	Eye Dam. 1: H318; Aquatic Acute 1: H400	<1%	

## Section 4: First aid measures

# 4.1. Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin.		
	Drench the affected skin with running water for 10 minutes or longer if substance is still		
	on skin. Transfer to hospital if there are burns or symptoms of poisoning.		
Eye contact:	Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist		
	examination.		
Ingestion:	Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10		
	minutes. If unconscious, check for breathing and apply artificial respiration if necessary.		
	If unconscious and breathing is OK, place in the recovery position. Transfer to hospital		
	as soon as possible.		
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. If		
	unconscious and breathing is OK, place in the recovery position. If conscious, ensure		

**Page:** 2

DRAINEX

Page: 3

the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and

provide oxygen if available. Transfer to hospital as soon as possible.

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

- **Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.
- **Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

DRAINEX

Page: 4

#### 6.4. Reference to other sections

## Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

**Respirable dust:** 

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

8.1. Control parameters

#### Hazardous ingredients:

#### SODIUM HYDROXIDE

#### Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m3	-	-

**DNEL/PNEC** Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:Ensure there is sufficient ventilation of the area.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Impermeable gloves.Eye protection:Tightly fitting safety goggles. Ensure eye bath is to hand.Skin protection:Impermeable protective clothing.

# Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State:LiquidColour:ColourlessOdour:Characteristic odourEvaporation rate:No data available.Oxidising:No data available.Solubility in water:Miscible

DRAINEX

			•
Viscosity:	Non-viscous		
Kinematic viscosity:	0.658		
Viscosity test method:	Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)		
Boiling point/range°C:	100	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	No data available.	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	Not applicable.	pH:	>11.5
VOC g/l:	No data available.		
9.2. Other information			

Other information: Not applicable.

# Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

# 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# Section 11: Toxicological information

11.1. Information on toxicological effects

## Hazardous ingredients:

#### SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

Page: 5

# SAFETY DATA SHEET DRAINEX

### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

#### Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

**Ingestion:** Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

#### Section 13: Disposal considerations

13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

#### Section 14: Transport information

DRAINEX

Page: 7

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: |

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 1

#### Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Safety, Health and Welfare at Work Act 2005 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2015 (SI 2015 No. 288) (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Commission Regulation (EU) No 2015/830 (as ammended).

Marine pollutant: No

15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

# Section 16: Other information

# Other information European Standards Referenced: I.S. EN 1146:2005 - Respiratory Protective Devices - Self-contained Open-circuit Compressed Air Breathing Apparatus Incorporating A Hood For Escape - Requirements, Testing, Marking EN 374-4:2013 Protective gloves against chemicals and micro-organisms - Part 4: Determination of resistance to degradation by chemicals

# DRAINEX

I.S. EN 166:2002 - Personal Eye-protection - Specifications.BS EN 464-1:1994 Protective Clothing For Use Against Liquid And Gaseous Chemicals,<br/>Including Aerosols And Solid Particles - Test Method: Determination Of Leak Tightness<br/>Of Gas Tight Suits (internal Pressure Test)Phrases used in s.2 and s.3:H314: Causes severe skin burns and eye damage.<br/>H315: Causes skin irritation.<br/>H318: Causes serious eye damage.<br/>H400: Very toxic to aquatic life.Legal disclaimer:The above information is believed to be correct but does not purport to be all inclusive<br/>and shall be used only as a guide. This company shall not be held liable for any<br/>damage resulting from handling or from contact with the above product.

# Page: 8