

PRODUCT DATA SHEET

EVERBUILD® Lead Mate® Patination Oil

A PROTECTIVE COATING ON ALL NEWLY FIXED LEADWORK

PRODUCT DESCRIPTION

EVERBUILD® Lead Mate® Patination Oil has been specially formulated to provide a protective coating for newly installed leadwork that helps to prevent the white carbonate staining that affects new lead and surrounding tiles, brickwork, stonework etc.

Just one coat of EVERBUILD® Lead Mate® Patination Oil also helps to provide uniform, attractive appearance to newly installed lead and helps the ageing process whilst the natural patina of the lead is being formed.

It is particularly important to treat areas of newly installed lead that are subject to water flowing over the surface onto surrounding areas as staining of tile and brick will be more severe in such circumstances.

USES

- Areas of newly installed lead that are subject to water flowing over the surface onto surrounding areas.
- Newly fixed lead work.

CHARACTERISTICS / ADVANTAGES

- Works on all newly fixed lead work.
- Prevent unsightly staining.
- Improves initial appearance and assists in natural ageing of lead.
- No spill pack for clean and easy application.

Boiling Point	152°C
Working Temperature	5 - 35°C (keep below flash point)
Coverage	Approximately 55-65 m ² / L

PRODUCT INFORMATION

Packaging	500ml and 1L Self-gaging plastic bottle
Appearance / Colour	Brown / Yellow liquid
Shelf Life	12 months from date of manufacture when stored as directed
Storage Conditions	Store in cool, dry conditions between +5 and +30°C. Ensure good ventilation. Storage outside these parameters will dramatically reduce shelf life.
Density	~0.8 g/cm ³
Flash Point	38°C

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Always wear gloves and only apply in a well ventilated area. Shake can well before use.
Surfaces must be totally dry before application.

APPLICATION METHOD / TOOLS

Apply oil evenly using a soft absorbent cloth, work horizontally starting at the top and maintain a wet edge at all times.

DO NOT APPLY IN A CIRCULAR MOTION AS THIS WILL LEAVE AN IMPRESSION ON THE LEAD.

Only one coat is required. Before clipping apply to underside of lead to approx 50mm from the edge. Apply to all areas, including clips and trim, and coat between

laps.

VERY IMPORTANT – Always apply as soon as possible after installation, or at the end of each working day, or if rain is expected apply before rain.

LIMITATIONS

- Do not allow EVERBUILD® Lead Mate® Patination Oil to come into contact with Bitumen or Polycarbonate sheets.
- Always test a small inconspicuous area prior to full application.
- As the company cannot be aware of all the applications and materials its product may be used on, it is the user's responsibility to determine suitability for use. Please contact Technical Services for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet
EVERBUILD® Lead Mate® Patination Oil
May 2019, Version 01.01
020516020000000020

EVERBUILDLeadMatePatinationOil-en-IE-(05-2019)-1-1.pdf

BUILDING TRUST

