

TIMCO MULTI-FIX POLYESTER STYRENE FREE RESIN

Page: 1

Compilation date: 15/02/2012

Revision date: 20/05/2014

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TIMCO MULTI-FIX POLYESTER STYRENE FREE RESIN

Product code: PESF310

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: A Chemical anchoring application

1.3. Details of the supplier of the safety data sheet

Company name: T.I.Midwood & Co Ltd

Green Lane Nantwich Cheshire CW5 6BJ

Tel: 44 (0) 1829 261111 **Fax:** 44 (0) 1829 261102

United Kingdom

Email: quality@timco.co.uk

1.4. Emergency telephone number

Emergency tel: 44 (0)1829 261111

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; Eye Irrit. 2: H319; Skin Sens. 1: H317

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



Precautionary statements: P264: Wash skin thoroughly after handling.

TIMCO MULTI-FIX POLYESTER STYRENE FREE RESIN

Page: 2

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

* Hazardous ingredients:

VINYL TOLUENE - REACH registered number(s): 01-21196222074-50-0000

EINECS	CAS	PBT / WEL	CLP Classification	Percent
246-562-2	25013-15-4	5-4 - Acute Tox. 4: H332; Asp		10-20%
		Eye Irrit. 2: H319; Flam. Liq. 3: H226		

2-ETHYLHEXYL BENZOATE

226-641-8	5444-75-7	-	Aquatic Chronic 4: H413	1-3%	

DIBENZOYL PEROXIDE BPO - REACH registered number(s): 01-2119511472-50-XXXX

202-327-6	-	-	Aquatic Acute 1: H400; Eye Irrit. 2:	
			H319; Org. Perox. B: H241; Skin Sens.	
			1: H317	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and

footwear immediately unless stuck to skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: If conscious, give half a litre of water to drink immediately. Do not induce vomiting.

Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Harmful if swallowed.Inhalation: Hamful by inhalation.

TIMCO MULTI-FIX POLYESTER STYRENE FREE RESIN

Page: 3

Delayed / immediate effects: Not applicable.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Dry chemical

powder. Carbon dioxide. Do not use halons.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Sealed, heated containers can pressurise leading to explosion. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container. Wash the area with water.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Keep away from Heat and sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Ensure lighting and electrical equipment are not a source of ignition. Store in a cool, well

ventilated area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Building and construction work (SU19).

Section 8: Exposure controls/personal protection

TIMCO MULTI-FIX POLYESTER STYRENE FREE RESIN

Page: 4

8.1. Control parameters

Hazardous ingredients:

DIBENZOYL PEROXIDE BPO

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3	•	-	•

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is exhaust ventilation of the area. Ensure all engineering measures

mentioned in section 7 of SDS are in place.

Respiratory protection: * Breathing protection is required in inadequately ventilated places. Gas/vapour filter,

type A: organic vapours (EN141).

Hand protection: * Protective gloves. Wear solvent proof gloves. Nitrile gloves. Rubber gloves.

Recommended thickness of material >0.4 mm. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in

advance and has therefore to be checked prior to the application.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Various

Odour: Sweet-smelling

Oxidising: Oxidising (by EC criteria)

Solubility in water: Insoluble

Relative density: 1.56 VOC g/l: 2.31

9.2. Other information

Other information: * Solid suspension - classified as non-flammable according to results from Test N.1

test method for readily combustible solids.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

TIMCO MULTI-FIX POLYESTER STYRENE FREE RESIN

Page: 5

10.2. Chemical stability

Chemical stability: Stable under normal conditions. May polymerise on heating.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Reducing agents. Amines. Acids. Alkalis. Heavy metal compounds.

10.6. Hazardous decomposition products

Haz. decomp. products: If exposed to high temperatures it will emit hazardous fumes and smoke.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIBENZOYL PEROXIDE BPO

ORL	RAT	LD50	5000	mg/kg
VAPOURS	RAT	LD50	24.3	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Harmful if swallowed.Inhalation: Hamful by inhalation.

Delayed / immediate effects: Not applicable. **Other information:** Not applicable.

Section 12: Ecological information

12.1. Toxicity

TIMCO MULTI-FIX POLYESTER STYRENE FREE RESIN

Page: 6

Hazardous ingredients:

DIBENZOYL PEROXIDE BPO

ALGAE	72H ErC50	0.0711	mg/l
Daphnia magna	48H EC50	0.110	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	0.0602	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company. Small quantities of the product can be mixed and allowed to cure, then can be

disposed as solid waste.

Waste code number: 08 04 12

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

TIMCO MULTI-FIX POLYESTER STYRENE FREE RESIN

Page: 7

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Active Oxygen Content of Catalyst Component 0.99%

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H241: Heating may cause a fire or explosion.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H400: Very toxic to aquatic life.

H413: May cause long lasting harmful effects to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.

ENVIRONMENTAL CARE: Please do not dispose of uncured material. If disposing

please mix any waste product to its cured state.