



HAILO G60

The aluminium multipurpose scaffold with "Fast & Lock" closure for fast and easy assembly.





THE KEY FEATURES

- Scaffold and ladder in one
- Easy to handle and fitted with "Fast & Lock" closure for fast, easy assembly
- Multipurpose: for use as a lean-to ladder and double ladder, as a small scaffolding unit for indoors and outdoors or as a platform for working
- Step adjustment option
- 2 ladder sections of 12 rungs (27 × 27 mm) with safety joints for locking/releasing the ladder sections
- Working platform with access hatch (61 × 46 cm)
- 2 crosspieces incl. 2 transport castors
- 4 guard rails and 4 aluminium diagonal struts



OTHER PRODUCT ADVANTAGES






- Platform dimensions: 136 × 50 cm
- Upright dimensions: 60 × 22 mm
- Rung spacing: 260 mm
- Maximum load capacity 150 kg/m²







SPECIFICATIONS

| | | |
|---|---|----------------------------------|
| Level of equipment | | 3 |
| Can be used in a free-standing position | | ✓ |
| Working platform | | ✓ |
| Step adjustment | | ✓ |
| Ladder sections can also be used on their own | | ✓ |
| Movable | | ✓ |
| Dimensions of packaging (HxWxD) |  | A = 166 cm, B = 60 cm, C = 35 cm |
| Platform height |  | 233 cm |
| Max. working height |  | 433 cm |
| Step adjustment max. | | 24 cm - 28 cm |
| Weight |  | 31,0 kg |
| Load capacity |  | 150 kg/m ² |