





Overview

PALTOP offers a cost-efficient solution for lightweight exterior roofing applications. It has a builtin ability to withstand all weather conditions.

PALTOP also has a smooth and attractive appearance, and offered in black or a range of vivid, non-fading colors. Its good impact resistance and low weight makes PALTOP easy to handle and ideal for a variety or roofing applications around the house.

Main Benefits

- Ideal for lightweight roofing
- Good impact resistance
- Suitable for all weather conditions
- Suitable for curved roofing
- Colors will not fade
- Provides thermal insulation
- Environmentally friendly -Does not contain any heavy metals
- 5 year warranty
- User friendly Easy to install

Typical Application

- Lightweight roofing
- Awnings
- Pergolas
- Private parking
- Sheds

PALTOP™ is lead free and does not contain any other heavy metals.



www.palram.com



Standard Dimensions*

Туре	Color Range		Profile		Thickness mm	Width mm	Length m
PALTOP™ Premuim		Grey, Green, Red, Black	70/18 (Greca/Trapeze)	~~~~	1.2	900	2-6
PALTOP™		Black	76/18 (Iron/Sinus)	~~~	1.2	900	2 - 6

^{*} Other options are available upon special request and are subject to a minimum quantity.

Typical Physical Properties

Property	(ASTM M	1ethod)	Conditions	Units	Value
Density (D-1505)				g/cm³	0.9
HBU* (Heat b	uildup)		$^{\circ}C$	<33	
Tensile streng	th at yield	(D-638)	10 mm/min	MPa	25
Tensile strength at break		(D-638)	10 mm/min	MPa	20
Elongation at yield		(D-638)	10 mm/min	%	1.4
Elongation at break		(D-638)	10 mm/min	%	7.0
Modulus of elasticity		(D-638)	1 mm/min	MPa	1480
Water absorption		(D-570)	24hr @ 23°C	%	<0.2

^{*} Heat Buildup = The increase of temperature that the product is able to withstand on top of the environment's temperature. In the test, 12x12cm samples of PALTOP were exposed to IR2 250W lamp at a 30cm distance.

Warranty

PALTOP sheets are guaranteed to resist breakage for 5 years in accordance with DIN EN 1013-3. PALTOP will also retain its fire resistance and weatherability for a long period. This warranty will only be valid if PALTOP is handled, stored, cleaned, installed and maintained in accordance with Palrams guidelines.

Weatherability

Improved weather resistance makes PALTOP suitable for exterior applications in all climates.



PALRAM H.Q.

Tel: +972 4 8459900 Fax: +972 4 8444012 palram@palram.com www.palram.com

PALRAM EUROPE LTD.

Tel: +44 1302 380777 Fax: +44 1302 380788 sales.europe@palram.com www.palram.com

PALRAM AMERICAS

Tel: 610 2859918 Fax: 610 2859928 palramamericas@palram.com www.palramamericas.com





