


## Concrete Screw - Countersunk

**Yellow**




**CORROSION RATING**

1 2 3 4 5

Clean, dry & low humidity environments

**Zinc**




**CORROSION RATING**

1 2 3 4 5

Clean, dry & low humidity environments


**Exterior (SO)**



**CORROSION RATING**

1 2 3 4 5

Urban & industrial areas with a low salt atmosphere



A rapid and effective light duty anchoring system for fixing into concrete, brick, stone, concrete block and wood. This through fixing provides a single solution and replaces traditional fixings such as nylon frame and hammer fixings.



• Conforms to BS 7671:2018



### Technical Data

Substrate	Concrete ≥25N/mm <sup>2</sup>		Fletton Brick 30N/mm <sup>2</sup>		Cheshire Brick 45N/mm <sup>2</sup>		Class B Eng. Brick 75N/mm <sup>2</sup>	
	40-70	80-200	40-80	80-200	40-70	80-200	40-70	80-200
Length (mm)	40-70	80-200	40-80	80-200	40-70	80-200	40-70	80-200
Drill Hole Ø (mm)	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
Min. Embedment Depth (mm)	35	50	35	50	35	50	35	50
Min. Drill Hole Depth (mm)	45	60	40	60	40	60	40	60
Rec. Tensile Load (kN)	1.07	1.82	1.17	1.79	0.75	1.46	0.85	1.22
Max Rec. Load (kg)	107	182	117	179	75	146	85	122


## Cover Caps (for Countersunk screws only)



Product Code	Colour	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
<b>BAG</b>				
CAPW100	White	100	100	360
CAPO100	Light Oak	100	100	360
CAPM100	Mahogany	100	100	360
TYPE - CON		SUB TYPE - CON01		

## Concrete Screw - Pan Head

**Zinc**



**CORROSION RATING**

1 2 3 4 5

Clean, dry & low humidity environments

**TX DRIVE**

TX DRIVE

**All Steel Non-Flammable Fixing**

A rapid and effective light duty anchoring system for fixing into concrete, brick, stone, concrete block and wood. This through fixing provides a single solution and replaces traditional fixings such as nylon frame and hammer fixings. Zinc plated with a pan head to improve clamping.

• Conforms to BS 7671:2018

Product Code	Size (mm)	Driver Bit Size	Max. Fixture Thickness (mm)	Fixture Clearance Hole Ø (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
<b>BOX (TX30 DRIVER BIT INCLUDED)</b>							
7580MFPAN	7.5 x 80	TX30	30	8.0	100	10	360
75100MFPAN	7.5 x 100	TX30	50	8.0	100	10	360
75120MFPAN	7.5 x 120	TX30	70	8.0	100	8	288
TYPE - CON		SUB TYPE - CON03					

Product Code	Size (mm)	Driver Bit Size	Max. Fixture Thickness (mm)	Fixture Clearance Hole Ø (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
<b>YELLOW</b>							
<b>BOX (TX30 DRIVER BIT INCLUDED)</b>							
00040TCON	7.5 x 40	TX30	5	8.0	100	18	648
00050TCON	7.5 x 50	TX30	15	8.0	100	12	432
00060TCON	7.5 x 60	TX30	25	8.0	100	10	360
00070TCON	7.5 x 70	TX30	35	8.0	100	10	360
00080TCON	7.5 x 80	TX30	30	8.0	100	10	360
00090TCON	7.5 x 90	TX30	40	8.0	100	10	360
00100TCON	7.5 x 100	TX30	50	8.0	100	10	360
00110TCON	7.5 x 110	TX30	60	8.0	100	10	360
00120TCON	7.5 x 120	TX30	70	8.0	100	8	288
00130TCON	7.5 x 130	TX30	80	8.0	100	8	288
00150TCON	7.5 x 150	TX30	100	8.0	100	8	288
00180TCON	7.5 x 180	TX30	130	8.0	100	6	216
00200TCON	7.5 x 200	TX30	150	8.0	100	6	216
<b>TIMBAG</b>							
00050TCONB	7.5 x 50	TX30	15	8.0	100	5	
00060TCONB	7.5 x 60	TX30	25	8.0	85	5	
00070TCONB	7.5 x 70	TX30	35	8.0	75	5	
00080TCONB	7.5 x 80	TX30	30	8.0	65	5	
00100TCONB	7.5 x 100	TX30	50	8.0	55	5	
00120TCONB	7.5 x 120	TX30	70	8.0	45	5	
00150TCONB	7.5 x 150	TX30	100	8.0	30	5	
<b>TIMPAC</b>							
00050TCONP	7.5 x 50	TX30	15	8.0	8	10	
00060TCONP	7.5 x 60	TX30	25	8.0	6	10	
00070TCONP	7.5 x 70	TX30	35	8.0	5	10	
00080TCONP	7.5 x 80	TX30	30	8.0	5	10	
00100TCONP	7.5 x 100	TX30	50	8.0	4	10	
00120TCONP	7.5 x 120	TX30	70	8.0	3	10	
00150TCONP	7.5 x 150	TX30	100	8.0	2	10	
TYPE - CON/BAG/PAK		SUB TYPE - CON01/BAG31/PAK44					
<b>Zinc</b>							
<b>BOX (TX30 DRIVER BIT INCLUDED)</b>							
00080TCONZ	7.5 x 80	TX30	30	8.0	100	10	360
00100TCONZ	7.5 x 100	TX30	50	8.0	100	10	360
00120TCONZ	7.5 x 120	TX30	70	8.0	100	8	288
00150TCONZ	7.5 x 150	TX30	100	8.0	100	8	288
TYPE - CON		SUB TYPE - CON03					
<b>Exterior (Silver Organic)</b>							
<b>BOX (TX30 DRIVER BIT INCLUDED)</b>							
80TCONR	7.5 x 80	TX30	30	8.0	100	10	360
100TCONR	7.5 x 100	TX30	50	8.0	100	10	360
120TCONR	7.5 x 120	TX30	70	8.0	100	8	288
TYPE - CON		SUB TYPE - CON02					